



TC-H363U Spec:W/4G/U/SE/4mm/V4.1

PT Camera

Wi-Fi Series



KEY FEATURES

- Plastic housing
- Up to Panorama:3MP,2304×1296@15fps Detail:3MP, 2304×1296@15fps
- S+265/H.265
- Color:0.0004Lux@(F1.0,AGC ON)
- 1×Built-in Mic, 1×Built-in Loudspeaker
- Support microSD/microSDHC/microSDXC card,up to 256GB
- Operating conditions -10°C~50°C(14°F~122°F), ≤95%RH
- DC5V±25%,Max. 10W
- IP65

SPECIFICATIONS

Camera	
Image Sensor	Panorama: 1/2.9"CMOS Detail: 1/2.9"CMOS
Min. Illumination	Color:0.0004Lux@(F1.0,AGC ON)
Shutter Time	1s~1/100000s
Day&Night	Fixed IR-cut
WDR	DWDR
S/N	>50dB
Angle Adjustment	Panorama:-60~60°(P) Details:0~345°(P); Panorama:5~15° Details:-15~90°
Lens	
Lens Type	Fixed focal lens
Focal Length	Panorama: 4mm Detail: 4mm
Lens Mount	M12
Aperture Range	Panorama: F1.0 Detail: F1.0
Aperture Type	Fixed
Field of View	Panorama:81.8°(H); Detail:81.8°(H); Panorama:44.9°(V); Detail:44.9°(V); Panorama:94.9°(D); Detail:94.9°(D)
DORI Distance	Panorama: Detect:57.14m Observe:22.68m Recognize:11.43m Identify:5.71m Detail: Detect:57.14m Observe:22.68m Recognize:11.43m Identify:5.71m
Pan&Tilt	
Pan Speed	30°/s
Tilt Speed	25°/s
Preset	255
Illuminator	
White LEDs	Panorama:4 Detail:4
Whitelight Distance	20m

Red and Blue Alarm Flash	Yes
--------------------------	-----

Compression Standard

Video Compression	S+265/H.265
Video Bit Rate	1.5M
Audio Compression	G.711A
Audio Sampling Rate	16kHz

Image

Max. Resolution	Panorama:3MP,2304×1296@15fps Detail:3MP,2304×1296@15fps
-----------------	--

Main Stream	Panorama: PAL:15fps(2304×1296) NTSC:15fps(2304×1296) Detail: PAL:15fps(2304×1296) NTSC:15fps(2304×1296)
-------------	--

Sub Stream	Panorama: PAL:15fps(704×576) NTSC:15fps(704×480) Detail: PAL:15fps(704×576) NTSC:15fps(704×480)
------------	--

AGC	Yes
-----	-----

3D DNR	Yes
--------	-----

White Balance	Auto
---------------	------

OSD	16*16/32*32/48*48; Lattice
-----	----------------------------

Feature

Exceptions Alarm	Disk Full; Disk R/W Error
Linkage Method	Trigger Sound; Trigger Warmlight; Trigger Recording; Trigger Capture
Auto-Tracking	Auto-Tracking

Network

Protocols	TCP; UDP; ICMP; DNS; NTP; IPv4; SSH; Unicast
System Compatibility	SDK
Remote Connection	≤2
Client	Easy7 VMS
Mobile Client	EasyLive Plus

Interface

Built-in Mic	1×Built-in Mic
Built-in Speaker	1×Built-in Loudspeaker
Reset Button	Yes
On-board Storage	Support microSD/microSDHC/microSDXC card,up to 256GB

General

Operating Temperature	-10°C~50°C(14°F~122°F)
Operating Humidity	≤95%RH
Storage Temperature	-10°C~50°C(14°F~122°F)
Storage Humidity	10%~95%RH(non-condensing)
Power Supply	DC5V±25%,Max. 10W
Protection	Surge500V; ESD6000V; IP65
Boundary Dimensions	183(L)105(W)202(H)mm
Package Dimensions	265(L)195(W)285(H)mm
GrossWeight	1.66kg

DIMENSIONS (Unit: mm)

